
**Packaging — Complete, filled transport
packages and unit loads — Low pressure
test**

*Emballages — Emballages d'expédition complets et pleins et charges
unitaires — Essai à basse pression*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 2873:2000

© ISO 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 734 10 79
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 2873 was prepared by Technical Committee ISO/TC 122, *Packaging*, Subcommittee SC 3, *Performance requirements and tests for means of packaging, packages and unit loads (as required by ISO/TC 122)*.

This third edition cancels and replaces the second edition (ISO 2873:1985) which has been technically revised.

Annex A of this International Standard is for information only.

Introduction

It is the responsibility of the user of this International Standard to establish appropriate health and safety practice in accordance with relevant legislation.

STANDARDSISO.COM : Click to view the full PDF of ISO 2873:2000

Packaging — Complete, filled transport packages and unit loads — Low pressure test

1 Scope

This International Standard specifies a method for subjecting complete, filled transport packages and unit loads to conditions of low air pressure similar to those encountered in aircraft.

This method is applicable to complete, filled transport packages and unit loads which are intended to be transported in pressurized aircraft flying at any altitude and in unpressurized aircraft flying at 3 500 m or less.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 2206, *Packaging — Complete, filled transport packages — Identification of parts when testing*.

ISO 2233, *Packaging — Complete, filled transport packages and unit loads — Conditioning for testing*.

3 Term and definition

For the purposes of this International Standard, the following term and definition applies.

3.1

test item

a complete filled transport package or unit load

4 Principle

The test item is placed in a pressure chamber, and the pressure in the chamber reduced to that corresponding to an altitude of 3 500 m. This pressure is approximately equal to that in pressurized aircraft flying at any higher altitude. The pressure is then held for a predetermined period after which it is permitted to return to ambient pressure.

NOTE While the pressure is held for the predetermined period, the temperature may also be maintained to that corresponding to the same altitude (see annex A, Table A.1).

5 Apparatus

5.1 Pressure vessel, of sufficient size to accommodate the test item, with pressure and temperature controls to meet the requirements of the procedure in clause 8.

6 Test item preparation

Fill the test item with its intended contents and ensure that the test item is closed normally, as if ready for distribution.

NOTE Simulated or substitute contents may be used on condition that the dimensions and physical properties of such contents are as close as possible to those of the intended contents. However, the closure should be the same as for distribution.

7 Conditioning

The test item shall be conditioned in accordance with one of the conditions described in ISO 2233.

8 Procedure

8.1 Place the test item in the pressure vessel (see clause 5) and reduce the pressure at a rate not exceeding 150 mbar/min, until it reaches 650 mbar ($\pm 5\%$). Maintain this pressure for the predetermined period.

NOTE 1 mbar = 1 hPa = 0,1 kPa

8.2 Restore the pressure by allowing dry air at laboratory temperature to enter at such a rate that the increase in pressure does not exceed 150 mbar/min.

NOTE If it is desired to study the effects of temperature as well as pressure in pressurized aircraft, the atmosphere in the vessel should be maintained at $(-8 \pm 1)^\circ\text{C}$ during the predetermined period.

9 Test report

The test report shall include:

- a) a reference to this International Standard;
- b) the name and address of testing laboratory and name and address of customer;
- c) the unique identification of the report;
- d) the date of receipt of the test items and the date(s) of performance of the test;
- e) the name, title and signature of persons accepting test responsibility for the test report;
- f) a statement to the effect that the test results relate only to the items tested;
- g) a statement that the report shall not be reproduced, except in full, without the written approval of the testing laboratory;
- h) the number of replicate test items tested;

- i) a full description, including dimensions, structural and material specifications of the test item and its fittings, cushioning, blocking, closure and reinforcing arrangements, gross mass of the test item and the mass of the contents in kilograms;
- j) the description of contents, if simulated or substituted contents were used, full details shall be given;
- k) the relative humidity, temperature and time of conditioning; the temperature and relative humidity of the test area at the time of test; whether these values comply with the requirements of ISO 2233;
- l) the attitudes in which the test item was tested, using the method of identification given in ISO 2206;
- m) the temperature and pressure inside the pressure vessel, and the time for which they were maintained;
- n) any deviation from the test method described in this International Standard;
- o) a record of the result, including any observations which assist in the correct interpretation of the results.

STANDARDSISO.COM : Click to view the full PDF of ISO 2873:2000