

AEROSPACE RECOMMENDED PRACTICE

REV. B **ARP1894** Issued 1987-02 1998-03 Revised Reaffirmed 2013-12 Stabilized 2014-02 Superseding ARP1894A

Useful Life Determination for Chemical Oxygen Generators

RATIONALE

The sponsoring Committee believes the technical content of this document is stable in nature and there are unlikely to be technology developments that would alter or reduce the utility of the present technical content.

STABILIZED NOTICE

This document has been declared "Stabilized" by the SAE A-10 Aircraft Oxygen Equipment Committee and will no longer SAENORM. CHICK to view the full Pr be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2014 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: 877-606-7323 (inside USA and Canada) Tel:

+1 724-776-4970 (outside USA) Tel: Fax: 724-776-0790

Email: CustomerService@sae.org

SAE WEB ADDRESS: http://www.sae.org http://www.sae.org/technical/standards/ARP1894B

SAE values your input. To provide feedback on this Technical Report, please visit

1. SCOPE:

The scope of this document is to provide a guideline for the preparation of a plan for testing of inservice chemical oxygen generators to confirm their design useful life. The test program should also allow determination with a sufficient level of confidence, whether generators are suitable for further use (i.e., life extension, or if the useful life limit has been reached).

2. REFERENCES:

2.1 Applicable Documents:

The following publications form a part of this document to the extent specified herein. The latest issue of SAE publications shall apply. The applicable issue of other publications shall be the issue in effect on the date of the purchase order. In the event of conflict between the text of this document and references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

2.1.1 SAE Publications: Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

AS1303 Portable Chemical Oxygen

AS1304 Continuous Flow Chemical Oxygen Generators

ARP1320 Determination of Chlorine in Oxygen from Solid Chemical Oxygen Generators

AS8010 Aviator's Breathing Oxygen (ABO) Purity Standard

2.1.2 FAR Publications: Available from Federal Aviation Administration, 800 Independence Avenue, SW, Washington, DC 20591.

FAR PART 23 Airworthiness Standards, Normal, Utility, Acrobatic and Commuter FAR PART 25 Airworthiness Standards, Transport Category Aircraft

2.1.3 U.S. Government Publications: Available from DODSSP, Subscription Services Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

49 CFR 172.102 (c)(i) Special Provision 60

49 CFR Chapter 1, Subchapter C - Hazardous Material Regulations

2.1.4 ATA Publications: Available from Air Transport Association of America, 1301 Pennsylvania Avenue, NW, Washington, DC 20004-1707.

ATA 300 Packaging of Airline Supplies

2.1.5 Airframe Manufacturer's Documents, or Supplier's Document, as applicable:

Item Specification Control Document

Quality Assurance Acceptance Test Procedures

Qualification Test Procedures

- 2.2 Definitions:
- 2.2.1 USEFUL LIFE: The useful life of a generator is defined as the sum of the shelf life and the service life from the time of manufacture.
- 2.2.2 FAMILY: A group of chemical oxygen generators having different part numbers, whose designs are sufficiently similar that factors affecting the useful life of one member of the group would reasonably be expected to affect all members in an analogous manner.
- 3. TECHNICAL REQUIREMENTS:
- 3.1 General Requirements:
- 3.1.1 Program: A test program shall be prepared using an appropriate methodology which evaluates the current performance of the generator against its original lot acceptance test data to determine any changes in performance that would constitute a trend that might affect the intended purpose.

3.1.2 Test Units: Specific part numbers shall be included in the test program (test articles). The test units shall be supplied by aircraft operators from in-service airplanes. If possible, generators should be identified as to what type of aircraft and where generator was installed.

Test articles should be packaged for shipment in a manner which adequately protects them from shipping damage and complies with relevant regulations.

- Representative Sampling: The number of units in the test sample should be no less than the original lot acceptance test quantities for all types of a typical lot size. The program should also include testing of generators of a representative sampling of a given year's production of a particular part number, to provide a level of confidence sufficient to permit the units to be used for PDFofark an additional specified time period.
- 4. TEST PLAN:
- 4.1 Pre-Test Inspection:
- 4.1.1 Visual: Each generator shall be initially inspected for visual evidence of corrosion, damage, degradation, contamination and evidence of improper handling.
- Radiographic: The internal condition of each generator shall be examined and recorded radiographically. It shall be done in at least 2 planes, 90° apart. Penetrations shall be done accordingly to best depict internal conditions.
- Electrical: If applicable, electrical and continuity checks shall be performed on each generator. Caution shall be exercised to not exceed the trigger current of the generator.
- 4.2 Test Requirements:

The units submitted for testing shall be tested in accordance with the following program. Refer to the appropriate Acceptance Test Procedure for the actual values and methodology.

- 4.2.1 Flow Performance Tests: One half of the sample size shall be divided as listed following and tested for (but not limited to):
 - a. Generator ignition and flow start
 - b. Flow rate and duration (profile)
 - c. Outlet manifold surface temperature (if applicable)
 - d. Housing temperature(s) (if applicable)
 - e. Weight change
 - f. Release pin pull force (as applicable)