

SAE-AS24333

ADOPTION NOTICE

SAE-AS24333, "Coupling Assembly, Hydraulic, Self-Sealing, Quick Disconnect, Flared Fitting to Internal Thread Boss," was adopted on 8 September 1998, for use by the Department of Defense (DoD). Proposed changes by DoD activities must be submitted to the DoD Adopting Activity: Commander, Naval Air Warfare Center Aircraft Division, Code 414100B120-3, Highway 547, Lakehurst, NJ 08733-5100. DoD activities may obtain copies of this standard from the DODSSP, Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094. The private sector and other government agencies may purchase copies from SAE, 400 Commonwealth Drive, Warrendale, PA 15096.

SAE-AS24333 should be used instead of MS24333.

Custodians:

Army - AV
Air Force - 99

Adopting Activity

Navy - AS
(Project 4730-1028)

SAENORM.COM : Click to view the full PDF of as24333

FSC 4730

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Submitted for recognition as an American National Standard

FEDERAL SUPPLY CLASS
4730**AS24333**


NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS24333F AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS24333F. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS TECHNICAL REPORT.

THIRD ANGLE PROJECTION



PREPARED BY COMMITTEE G-3

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

COUPLING ASSEMBLY, HYDRAULIC,
SELF-SEALING, QUICK DISCONNECT,
FLARED FITTING TO INTERNAL THREAD BOSS

AS24333
SHEET 1 OF 3

ISSUED 1998-08

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright 1998 Society of Automotive Engineers, Inc.
All rights reserved.

Printed in the U.S.A.

QUESTIONS REGARDING THIS DOCUMENT: (724) 772-8510
TO PLACE A DOCUMENT ORDER: (724) 776-4970


FA Distributed under license from the IHS Archive ADDRESS:
FA : (724) 776-0790

<http://www.sae.org>

SAENORM.COM : Click to view the full PDF of as24333

AS24333

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL-C-25427.



DASH NO.	TUBE OD INCH	THREAD T MIL-S-8879	A DIA $\pm .015$	B DIA MAX	C $\pm .010$	D $\pm .010$	E	F MIN	G $+.016$ $-.000$	H MAX	J $+.032$ $-.062$	J ₁ MAX	K DIA MAX
-4	.250	.8750-14 UNJ-3A	.750	1.000	.594		1.125	+.003		1.384	3.175	3.769	1.625
-6	.375	1.0625-12 UNJ-3A	.875	1.250			1.375	-.004		1.910	3.566	4.222	1.312
-8	.500	1.3125-12 UNJ-3A	1.063	1.500	.718	.030	1.625		.355	1.848	3.990	4.659	1.937
-10	.625		1.125	1.894	.781			$\pm .016$		1.938	4.640	5.515	2.125
-12	.750	1.6250-12 UNJ-3A	1.438	1.750	.906	.062	1.875			2.200	4.919	5.753	2.375
-16	1.000	1.8750-12 UNJ-3A	1.687	2.000	.938	.093	2.125		.438	2.803	5.827	6.847	2.625
-20	1.250	2.5000-12 UNJ-3A	2.000	2.375	.984	.125	2.750	$\pm .020$.500	2.900	6.727	7.897	2.675

AEROSPACE STANDARD

COUPLING ASSEMBLY, HYDRAULIC,
SELF-SEALING, QUICK DISCONNECT,
FLARED FITTING TO INTERNAL THREAD BOSS

AS24333
SHEET 2 OF 3