

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.  
B

AS5808

FEDERAL SUPPLY CLASS  
4730

## RATIONALE

AS5808B HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.





FIGURE 1 - TEE, FEMALE FLARELESS, SWAGE

SEE TABLE 1A THROUGH 1C FOR DIMENSIONAL AND WEIGHT INFORMATION

SAE values your input. To provide feedback  
on this Technical Report, please visit  
<http://www.sae.org/technical/standards/AS5808B>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3B

PROCUREMENT SPECIFICATION: AS5958 /4/



## AEROSPACE STANDARD

FITTING ASSEMBLY, TEE FEMALE  
FLARELESS AND AXIALLY SWAGED ON THE RUN,  
FEMALE FLARELESS ON THE BRANCH, HYDRAULIC, 3000 PSI

AS5808  
SHEET 1 OF 4

REV.  
B

Copyright 2015 SAE International  
All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)  
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)  
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

ISSUED 2008-06 REVISED 2009-05 REAFFIRMED 2015-04

TABLE 1A - DIMENSIONS A THROUGH H1

BASIC NO. AS5808 /14/ SIZE CODE	NOMINAL TUBE SIZE END 1	NOMINAL TUBE SIZE END 2	NOMINAL TUBE SIZE END 3	A ±.015	B MAX.	B1 MAX.	C ±.015.	E MAX.	F MIN.	G	(H)	(H1)
060606	.3750	.3750	.3750	1.040	1.215	1.099	1.040	.609	.378	.477-.509	.688	.688
060608	.3750	.3750	.5000	1.133	1.308	1.192	1.229	.609	.378	.615-.647	.688	.875
060808	.3750	.5000	.5000	1.133	1.516	1.370	1.229	.783	.504	.615-.647	.688	.875
080608	.5000	.3750	.5000	1.229	1.308	1.192	1.229	.609	.378	.615-.647	.875	.875
100812	.6250	.5000	.7500	1.560	1.704	1.558	1.592	.783	.504	.893-.925	1.000	1.250
101006	.6250	.6250	.3750	1.435	1.873	1.669	1.198	.939	.629	.751-.783	1.000	.688
101012	.6250	.6250	.7500	1.560	1.998	1.794	1.592	.939	.629	.893-.925	1.000	1.250
120812	.7500	.5000	.7500	1.592	1.704	1.558	1.592	.783	.504	.893-.925	1.250	1.250

TABLE 1B - DIMENSIONS J THROUGH T

BASIC NO. AS5808 /14/ SIZE CODE	NOMINAL TUBE SIZE END 1	NOMINAL TUBE SIZE END 2	NOMINAL TUBE SIZE END 3	J /10/ TUBE DEDUCT	K MAX.	K1 MAX.	M MIN.	N GAGE	N1 GAGE	P MIN.	T THREAD PER AS8879
060606	.3750	.3750	.3750	.416 ±.150	.337	.337	.045	.4160	.4160	.302	.5625-18UNJF-3B
060608	.3750	.3750	.5000	.509 ±.150	.337	.380	.052	.4160	.5600	.302	.5625-18UNJF-3B
060808	.3750	.5000	.5000	.517 ±.175	.337	.380	.052	.4160	.5600	.401	.5625-18UNJF-3B
080608	.5000	.3750	.5000	.509 ±.150	.380	.380	.052	.5600	.5600	.302	.7500-16UNJF-3B
100812	.6250	.5000	.7500	.705 ±.175	.407	.433	.065	.6860	.8100	.401	.8750-14UNJF-3B
101006	.6250	.6250	.3750	.580 ±.175	.407	.337	.057	.6860	.4160	.507	.8750-14UNJF-3B
101012	.6250	.6250	.7500	.705 ±.175	.407	.433	.065	.6860	.8100	.507	.8750-14UNJF-3B
120812	.7500	.5000	.7500	.705 ±.175	.433	.433	.065	.8100	.8100	.401	1.0625-12UNJ-3B

TABLE 1C - DIMENSIONS T1 THROUGH W4 AND WEIGHTS

BASIC NO. AS5808 /14/ SIZE CODE	NOMINAL TUBE SIZE END 1	NOMINAL TUBE SIZE END 2	NOMINAL TUBE SIZE END 3	T1 THREAD PER AS8879	W MIN.	W1 MAX.	W2 ±.0015	W3 MAX.	W4 MAX.	WEIGHT LB/EA APPROX. REF.
060606	.3750	.3750	.3750	.5625-18UNJF-3B	.153	.675	.4475	.033	.065	.093
060608	.3750	.3750	.5000	.7500-16UNJF-3B	.153	.675	.4475	.033	.065	.135
060808	.3750	.5000	.5000	.7500-16UNJF-3B	.165	.871	.5945	.033	.129	.151
080608	.5000	.3750	.5000	.7500-16UNJF-3B	.153	.675	.4475	.033	.065	.157
100812	.6250	.5000	.7500	1.0625-12UNJ-3B	.165	.871	.5945	.033	.129	.265
101006	.6250	.6250	.3750	.5625-18UNJF-3B	.140	1.190	.7365	.021	.078	.214
101012	.6250	.6250	.7500	1.0625-12UNJ-3B	.140	1.190	.7365	.021	.078	.358
120812	.7500	.5000	.7500	1.0625-12UNJ-3B	.165	.871	.5945	.033	.129	.380



## AEROSPACE STANDARD

FITTING ASSEMBLY, TEE FEMALE  
FLARELESS AND AXIALLY SWAGED ON THE RUN,  
FEMALE FLARELESS ON THE BRANCH, HYDRAULIC, 3000 PSI

AS5808  
SHEET 2 OF 4

REV.  
B

NOTES:

/1/ MATERIALS:

CODE LETTER "T"

RING - AMS4965 TITANIUM ALLOY, 6.0AL 4.0V SOLUTION HEAT TREATED AND AGED OR AMS4928 TITANIUM ALLOY 6.0AL 4.0V ANNEALED WITH HIGH STRENGTH CARBON FIBER/EPOXY RESIN COMPOSITE REINFORCEMENT.

BODY - AMS4928 TITANIUM ALLOY, 6.0AL 4.0V ANNEALED

NUT - AMS4965 TITANIUM ALLOY, 6.0AI 4.0V SOLUTION TREATED OR AMS4928 TITANIUM ALLOY, 6.0AL 4.0V ANNEALED.

WIRE - AMS5637 STEEL, CORROSION RESISTANT, 18CR - 9.0NI (UNS 30302) SOLUTION TREATED AND COLD DRAWN 125 ksi TENSILE STRENGTH

- AMS5685 STEEL, CORROSION RESISTANT, SAFETY WIRE 18CR - 11.5NI, 305 WIRE, SOLUTION TREATED, COLD FINISHED

- ASTM A 580 STEEL, CORROSION RESISTANT, WIRE, 302 OR 305 CONDITION A

2. FINISH:

TITANIUM - NONE REQUIRED

CRES - PASSIVATION PER AMS2700, TYPE 6 OR 7.

/3/ COATINGS/LUBRICANTS:

RING - THE OUTER SURFACE SHALL HAVE A .125 in MINIMUM WIDTH BLUE COLORED RING OR COMPLETELY COLORED BLUE TO MATCH THE ASSEMBLY TOOLING COLOR CODE SPECIFIED IN AS5959 ASSEMBLY PROCEDURE. AN AS1241 FLUID RESISTANT PTFE COATING OR PAINT SHALL BE USED. THE SWAGE RING IS COLOR CODED BLUE TO INDICATE THE AXIALLY SWAGE END IS QUALIFIED TO 5080 PSI AND IS INSTALLED WITH THE SAME TOOLING AS THE 5080 PSI RATED FITTING.

BODY - SOLID FILM LUBRICANT PER AS5272, TYPE I OR II, OR PTFE BASED LUBRICANT MAY BE APPLIED TO PORTIONS OF THE ID AND OD. THE AS5272 OR PTFE BASED LUBRICANT SHALL NOT BE IN CONTACT WITH THE SYSTEM FLUID.

NUT - LUBRICATE ID THREADS AND WIRE GROOVE LOAD BEARING SHOULDER OR MATING WIRE GROOVE LOAD BEARING SHOULDER WITH SOLID FILM LUBRICANT PER AS5272, TYPE 1 OR TYPE 2.

WIRE - LUBRICATE THE WIRE WITH SOLID FILM LUBRICANT PER AS5272, TYPE I OR TYPE II.

/4/ PRODUCT SPECIFICATION: AS5958 EXCEPT AS SPECIFIED ON THIS STANDARD. PRODUCT SUPPLIED TO THIS SPECIFICATION SHALL BE MANUFACTURED AND ASSEMBLED BY AN ACCREDITED MANUFACTURER OR ASSEMBLED BY AN ACCREDITED ASSEMBLING DISTRIBUTOR LISTED IN THE PERFORMANCE REVIEW INSTITUTE (PRI) QUALIFIED PRODUCTS LIST (QPL) PRI-QPL-AS5958 FOR THIS STANDARD. See [www.eauditnet.com](http://www.eauditnet.com) FOR THE CURRENT QPL ON-LINE.

5. DIMENSIONS AND TOLERANCES NOT DEFINED ON THIS STANDARD SHALL BE SPECIFIED AND CONTROLLED BY THE MANUFACTURER. THE MANUFACTURER IS RESPONSIBLE TO ENSURE COMPLIANCE WITH THE PROCUREMENT SPECIFICATION.

/6/ IDENTIFICATION SHALL BE IN ACCORDANCE WITH AS5958 AND SHALL BE IDENTIFIED ON RING.

7. FITTINGS SHALL BE INSTALLED IN ACCORDANCE WITH AS5959.

8. SURFACE TEXTURE SHALL BE IN ACCORDANCE WITH AMERICAN SOCIETY OF MECHANICAL ENGINEERS, ASME B46.1 AND THE SYMBOLS IN ACCORDANCE WITH ASME Y14.36M. UNLESS OTHERWISE SPECIFIED, THE MAXIMUM MACHINED SURFACES SHALL BE 125  $\mu$ in Ra AND THE FORGED SURFACES SHALL BE 250  $\mu$ in Ra.

	<b>AEROSPACE STANDARD</b>	<b>AS5808</b> SHEET 3 OF 4	<b>REV.</b> <b>B</b>
	FITTING ASSEMBLY, TEE FEMALE FLARELESS AND AXIALLY SWAGED ON THE RUN, FEMALE FLARELESS ON THE BRANCH, HYDRAULIC, 3000 PSI		